


Fixed Bollard - Monobloc Generation 6 Range



Monobloc Range

ACROPOLE

ATHÉNA

CHATEAUNEUF

CYLINDER

VENDÔME

Resistance	Weight
Depends on nature of embedding	44.9 to 154.32 lbs (Vendôme: 8.82 to 13.23 lbs)
Material	Thickness ><
Cast iron or Cast Steel depending on model – Vendôme: PG220 Stainless Steel	0"4331 (Vendôme: 0"0787)

DESCRIPTION

The « Generation 6 » monobloc® fixed bollard is available in 3 different diameters (4"72, 7"87 and 9"84) and 2 heights above ground level (19"68 and 29"52) (except for Vendôme's).

These bollards, in cast iron, cast steel or stainless steel, are embedded in concrete (see installation drawing). They may be extended, on option, and depending on the nature of soil.


The top may be circled with a reflective tape band (on option). These bollards are on average 0"43 thick, they are coated with thermosetting polyester powder paint.

Resistance to shocks and impacts of these products therefore largely depends on how firmly they are anchored into the ground.

The Chateaufort bollard is also available with a rounded top, a diameter of 4"72 and a height above ground level of 21"65, 29"52 and 37"40.

The Vendôme bollard is in stainless steel with PG220 finishing, >> 0"078. It exists with a diameter of 6"10 and 8"66 for a height above ground level of 19"68 and 29"52.

COLORS



Standard URBACO color: RAL 7016 (charcoal gray)

OPTIONS

- Colors: other RAL tones
- Reflective tape band (White – Red – Yellow)



Acropole bollard head

INSTALLATION PLAN

e.g.: Bollard, diam. 7"87, height 19"68

