



Connections from door panel to telephone

4+1 system cable size requirements

Connections	50mm	100mm	200mm	300mm	400mm
1	0.25mm ²	0.35mm ²	0.5mm ²	0.75mm ²	1.0mm ²
2	0.25mm ²	0.35mm ²	0.5mm ²	0.75mm ²	1.0mm ²
3	0.5mm ²	0.75mm ²	1.5mm ²	2.0mm ²	2.5mm ²
5	0.5mm ²	0.75mm ²	1.5mm ²	2.0mm ²	2.5mm ²
6	0.25mm ²	0.35mm ²	0.5mm ²	0.75mm ²	1.0mm ²

When ever possible connection 1 (TX) should be twisted with connection 3 (GND) and connection 2(RX) should be twisted with connection 3 (GND) as pairs. Maximum acceptable resistance for terminals 1,2&6 = 100 and for terminals 3&5 = 30.

connections for psu's

	50m	100mm	200mm	300mm	400mm
Connections	0.5mm	0.75mm	1.5mm	2.0mm	2.5mm

The power supply should be located as close to the door panel as possible for best performance. Maximum acceptable resistance for above cables = 30

VIDEX SECURITY LTD 

TECHNICAL HELP: TEL: 0191 224 3174
 FAX: 0191 224 3948
 EMAIL: tech@videx-security.com

DATE: 6/10/05 INITIAL: GN REF: VRDK1 (537)

DESCRIPTION: