

# TWO-LEAF SWING DOOR



## COMPONENTS

- A** Operator (garmotor and control board)
- B** PULL-TO-OPEN transmission lever
- C** PUSH-TO-OPEN transmission lever
- D** Card for emergency functioning during blackouts
- L** Control panel
- A** Command and safety radar
- B** Function selector
- C** Swipe sensor

## CABLES FOR A STANDARD INSTALLATION

CABLE LENGTH (m)	< 10	from 10 to 20	from 20 to 30
230 V AC power supply	3G x 1.5 mm <sup>2</sup>	3G x 1.5 mm <sup>2</sup>	3G x 2.5 mm <sup>2</sup>
Function selector	7 x 0.5 mm <sup>2</sup>	7 x 0.5 mm <sup>2</sup>	7 x 0.5 mm <sup>2</sup>
12 - 24 V AC - DC swipe sensor	4 x 1 mm <sup>2</sup>	4 x 1 mm <sup>2</sup>	4 x 1 mm <sup>2</sup>
Command devices	*n. x 0.5 mm <sup>2</sup>	*n. x 0.5 mm <sup>2</sup>	*n. x 0.5 mm <sup>2</sup>

\*n. = see product installation instructions - **Warning:** the cable section varies depending on the power of the motor and the length of the cable.