

The table shows all control panel features for overhead door-specific operators. Those in bold-type are important when selecting which operator to fit and should be considered from the start.



Models / Series	V900E	V700E	V6000				
Control board / Panel	ZL56	ZL56A	-				
Features	Safety						
SELF-DIAGNOSIS of safety devices							
PRE-FLASHING during opening and closing							
RE-OPENING during closing	●	●	●				
RE-CLOSING during opening							
Obstacle STALL							
TOTAL STOP	●	●	●				
PARTIAL STOP							
OBSTACLE DETECTION in front of photocells							
ENCODER	●	●	●				
MOVEMENT CONTROL and OBSTACLE DETECTION device							
AMPEROMETRIC DETECTION	●	●	●				
	Command						
PEDESTRIAN OPENING							
PARTIAL OPENING *	●*	●*					
ONLY-OPEN feature with transmitter and/or button							
Button connection for ONLY-OPEN or ONLY-CLOSE feature							
OPEN-STOP-CLOSE-STOP from transmitter and/or button	●	●	●				
OPEN-CLOSE-REVERSE from transmitter and/or button							
MAINTAINED ACTION							
DELAYED OPENING of 1st leaf							
DELAYED CLOSING of 2nd leaf							
IMMEDIATE CLOSING							
EMERGENCY RELEASE from transmitter							
	Characteristics and adjustments						
Output for connecting the FLASHING LIGHT	●	●	●				
Output for connecting the CYCLE LAMP							
Output for connecting the COURTESY LAMP	●	●					
Antenna	●	●	●				
Output for connecting the SIGNALLING LAMP (gate open)							
Output for connecting the SIGNALLING LAMP (gate closed)							
Contact output for 2nd RADIO CHANNEL							
OPERATION TIME adjustment							
SELF-LEARNING of transmitter RADIO CODE	●	●	●				
Output for connecting ELECTRIC LOCK and/or "HAMMER ACTION"							
Adjustable TIME before AUTOMATIC CLOSING	●	●	●				
Slow-down during OPENING and/or CLOSING	●	●	●				
EMERGENCY FUNCTIONING with batteries (optional)	●	●					
MASTER-SLAVE							
Adjustable SLOW-DOWN and FUNCTIONING speed							
DISPLAY						●	
Electronic BRAKE	●	●					
Endstop SELF-LEARNING of open and close positions	●	●	●				
SLEEP MODE							
Output for connecting the SOLAR PANEL							

● 24 V DC INTENSIVE SERVICE

NOTES

* Possibility of partial opening with button, switch or transmitter.